



Attn: City of Smyrna

I truly appreciate the opportunity to Partner with your and earn your truck business. Kenworth has built its brand on durable, vocational trucks that are engineered for the application. The Kenworth brand is proudly supported by MHC Kenworth, the largest Kenworth dealer group in the US with 100 locations in 16 states.

2021 Kenworth T880 Tandem Axle Dump

\$151,587.00

Engine Paccar MX-11

Please see attached spec for Chassis

- **State of Georgia Contract Number SPD0000155**

Sourcewell 

- **CONTRACT NUMBER 081716-KTC**

-Price Includes

7 Year 200,000 Mile Engine and After Treatment Extended Warranty

Ox Maverick Dump Body Please See Attached Specs

25 Ton Pintle Hitch

PDI and Delivery To City of Smyrna Location

-Price excludes any state or local sales tax

Current Chassis Build Date 9/7/2020

Estimated Delivery 12/7/2020

Support – Coverage across the State of Georgia:

Baxley – Open Mon-Fri 8am-5pm

Savannah-Open Mon-Fri 8am-8pm Sat 8am-4:30pm

Augusta- Open Mon-Fri 8am-5pm Sat 7am-4pm

Mableton – Open 24/7 Mon – Sunday

- Including mobile maintenance trucks available 24/7/365

Gainesville – Open 8 – 6 Mon – Sat

McDonough – Open 8 – 10pm Mon – Fri, 8 – 4pm Sat,

Conyers – Open 8 – 6pm Mon-Sat

Macon – Open 8 – 6pm Mon-Sat



**MHC Kenworth
Atlanta**

5860 Riverview Rd.

Mableton, Georgia 30126

A Division of Georgia Kenworth, Inc.

404.691.9999

404.691.0057 fax

www.mhctruck.com



Sincerely,

Byron Franklin New Truck Sales – Atlanta GA

7/28/2020



TRUCK BODIES & EQUIPMENT INTERNATIONAL, Inc.
Ox Bodies, Crystal, DuraClass, Rugby, J-Craft, Hardline

Ox Bodies INC
719 Columbus Street East
Fayette AL 35555
USA
800-844-2519

Quote Response Form

Page 1 of 2
07/15/2020 09:20 AM

End User: UNKNOWN
Customer: 35065

Byron Franklin
MHC KENWORTH ATLANTA
5860 RIVERVIEW ROAD SE
Location Code 50
Mableton GA 30126
USA

Phone: 706-847-0480
Fax: 14046910057

Taken By: Shannon Johnson

| Estimate | Terms | Quote Date | Expiration Date | Salesperson | Customer Currency |
|------------|--------------|------------|-----------------|---------------|-------------------|
| FA01037896 | Max 120 Days | 7/15/2020 | 8/14/2020 | MANN, CHARLES | USD |

| UM | Quantity | Item | Description | Unit Price | Extended Price |
|----|----------|---------|--------------------------------|------------|----------------|
| EA | 1.00 | 2284590 | MV851506-63130-56/42/50STR-2WY | 19,603.25 | 19,603.25 |

Body Type: Maverick
Length: 15'6"
Hoist: 63130 Parker
Side Height: 42"
Side Material: 10GA A36
T/G Type & Bracing: Two Way
T/G Material: 7GA A36
Floor Material: 1/4" AR450
Cabshield Size & Type: Full Width 24x85
Tarp: Vinyl w/ Flaps
Dump Apron Size & Type: 10" Heavy Duty
Boards Size & Type: 8" Wood
Lights: FMVSS
Body Color: Black
Trans Model: Allison
Pump: Air
Mud Flaps: 30" w/ Gravel Guards
Installed: Yes
Truck type: Kenworth

INSULATE BODY w/ ALUMINUM

| | | | | | |
|----|------|---------|--|----------|----------|
| EA | 1.00 | 2262591 | TARP ELEC-MOUNTAIN-10-16'-VNYL-W/FL-INST | 1,371.80 | 1,371.80 |
|----|------|---------|--|----------|----------|



TRUCK BODIES & EQUIPMENT INTERNATIONAL, Inc.
On Bodies | Crystal | DuraGlass | Playby | J-Craft | Mercedes

Ox Bodies INC
719 Columbus Street East
Fayette AL 35555
USA
800-844-2519

Quote Response Form

Page 2 of 2
07/15/2020 09:20 AM

End User: UNKNOWN
Customer: 35065

Byron Franklin
MHC KENWORTH ATLANTA
5860 RIVERVIEW ROAD SE
Location Code 50
Mableton GA 30126
USA

Phone: 706-847-0480

Fax: 14046910057

Taken By: Shannon Johnson

| Estimate | Terms | Quote Date | Expiration Date | Salesperson | Customer Currency |
|------------|--------------|------------|-----------------|---------------|-------------------|
| FA01037896 | Max 120 Days | 7/15/2020 | 8/14/2020 | MANN, CHARLES | USD |

| UM | Quantity | Item | Description | Unit Price | Extended Price |
|----|----------|------|-------------|------------|----------------|
|----|----------|------|-------------|------------|----------------|

Lift Axle:

Alignment of lift axle must be preformed by end user prior to the unit being placed in service. Failure to properly align the axle prior to being placed in service can cause non-warrantable failure, including but not limited to premature tire wear. The end user is responsible for the alignment prior to placing the unit in service.

PTO Maintenance:

Per OEM manufacturer guidelines the following recommendations should be followed. Failure to follow OEM guidelines can result in non warrantable failure.

Within the first week of use, recheck the installation of the PTO. Check for leaks and loose mounting hardware (studs, cap screws, nuts). Recheck the cable or lever connections for proper adjustment and tighten any loose connections. At regular maintenance intervals, check adjustments and lubricate moving parts, tighten and repair the connections, mounting hardware, cable or lever linkage. Refer to OEM owners manual for regular maintenance intervals.

**By signing below I acknowledge that I have reviewed the specs above and confirmed they are correct. I understand that once my order is placed and sent into production that I will not be able to make changes to the order. I assume full ownership of the body once production begins.

X _____

TRUCK YEAR/MAKE/MODEL _____ CLEAR CT: _____

VIN _____ TRANS _____

ETA _____ DUMP BODY COLOR _____

Pto switch in dash is recommended for all automatic or automated transmissions.

**Tractor valve must be in cab for glads to be plumbed **

Verify ship to address on quote.

| | |
|---------------|-----------|
| Gross Sales: | 22,079.00 |
| Order Disc | 1,103.95 |
| Sale Amount: | 20,975.05 |
| Freight: | 700.00 |
| Sales Tax: | 0.00 |
| FET Charges: | 0.00 |
| Total Amount: | 21,675.05 |



| Sales Code | Std/ Opt | Description | Weight |
|--------------|----------|---|--------|
| Model | | | |
| 0000810 | S | T880 Series Conventional | 14,844 |
| 0070060 | S | T880 | 0 |
| 0072000 | O | Chassis operation will not include a stationary application. Stationary operation is defined as running the engine under load while stationary at a substantial fraction of engine gross horsepower (60% or greater) for an extended period of time (longer than 5 - 10 minutes). | 0 |
| 0080066 | O | CARB Idle Emissions Reduction - MX | 0 |
| 0090000 | S | Non-Sleeper w/rear axle capacity less than 59K. | 0 |

Engine & Equipment

| | | | |
|---------|---|---|---|
| 0700197 | O | PACCAR MX-11 430 2017 430@1600 1650@900 with engine brake N08200 N052 650...IDLE TARGET N09020 N015 NO...ENABLE MX RETARDER IN NEUTRA N08020 N718 155...LRSL SPEED LIMIT N08030 N711 64...MAX PEDAL SPEED N09030 N874 0....ENG BRK DELAY TIME N09040 N871 2....DSC TGT VEH SPD LMT OFFSET N09050 N870 4....DSL TGT VEH SPD LIMIT OFFSET N09110 N506 10....CC MIN ENABLE SPD N09130 N890 MT....MULTI TORQUE IN CC N09120 N509 OFF...DYNAMIC CC ENABLE N09220 N690 5....EIST STANDSTILL IDLE TIME N09230 N689 5....EIST PARKED MAX IDLE TIME N09240 N692 YES...EIST ENG LOAD RESET N09250 N693 NO...EIST ENG LOAD OVERRIDE N09260 N688 5....EIST PTO MAX IDLE TIME N09270 N702 YES...EIST OVERRIDE IN PTO MODE N09280 N687 40....EIST AMB AIR TEMP OVERRIDE L N09290 N686 80....EIST AMB AIR TEMP OVERRIDE H N09300 N684 30....EIST CLNT TEMP OVERRIDE LO N09310 N699 YES...EIST ACCEL POSITION RESET N09320 N701 YES...EIST CLUTCH PEDAL RESET N09330 N700 YES...EIST FOOT BRK RESET N09340 N681 YES...EIST PARK BRK RESET ENABLE N09350 N726 1900..FIC MAX ENG SPEED N09400 N545 YES...CAB: ACCEL ACTIVE IN CAB PTO N09410 N578 YES...PTO REM PEDAL ENABLE N09420 N523 6....CAB: MAX VEH SPD N09430 N520 2000..CAB: MAX ENG SPD - SW CNTRL N09440 N519 2000..CAB: MAX ENG SPD-ACCEL CNTRL N09100 N504 64....CC MAX TARGET SPD N09450 N603 650...CAB: MIN ENG SPD N09510 N535 800...CAB: DEDICATED PRESET "-" N09520 N536 900...CAB: DEDICATED PRESET "+" | 0 |
|---------|---|---|---|

Printed January 1, 2020

Local T880 Conventional Dump

Printed On: 1/24/2020 8:40:11 AM

Date: January 24, 2020

Quote Number: QUOT-502661-1 (NOT)

| Sales Code | Std/ Opt | Description | Weight |
|----------------------------------|-------------|---|--------|
| 1000684 | O | Effective VSL Setting NA | 0 |
| 1000857 | S | Engine Idle Shutdown Timer Enabled | 0 |
| 1000891 | O | Eff EIST NA Expiration Miles | 0 |
| 1006003 | S | Air Compressor: WABCO 25.9 CFM PACCAR MX 2017 440cc Air Compressor | 0 |
| 1051200 | S | Air Cleaner: composite firewall mounted PACCAR or Cummins engines | 0 |
| 1105210 | S | Fan hub: Horton 2-Speed for PACCAR MX | 0 |
| 1123555 | S | Cooling module: 1330 square inches. Includes aluminum radiator core, aluminum charge air cooler, translucent surge tank and washer bottle, silicone hoses, and extended life coolant. | 0 |
| 1247166 | S | Exhaust: 2017 EPA RH Under DPF/SCR w/ RH side of cab vertical tailpipe w/ daycabs, extended daycabs, or modular sleepers. | 0 |
| 1290124 | O | Tailpipe: 5 in. single 24 in. 45 degree curved. | -3 |
| 1321100 | O | Fuel Filter: Customer Supplied or None Fuel/Water Separator. ISX12N Only. | 0 |
| 1321200 | O | Run Aid:None *For Fuel Filter | 0 |
| 1321300 | S | Start Aid:None *For Fuel Filter | 0 |
| 1504005 | O | Immersion block heater 120V 1500W w/plug under door on C500, T660, T800 & W900. | 2 |
| 1816260 | S | Alternator: PACCAR 160 amp, brush type | 0 |
| 1821210 | S | Batteries: 3 PACCAR GP31 threaded post (700-730) 2100-2190 CCA dual purpose. | 0 |
| 1836102 | S | PACCAR Premium 12V Starter with PACCAR MX Engines PACCAR 12 volt electrical system. With centralized power distribution incorporating plug-in style relays. Circuit protection for serviceability, 12- volt light system w/circuit protection circuits number & color coded. | 0 |
| 1840005 | O | Battery disconnect switches 2, mounted on battery box. | 2 |
| 1840065 | S | 12V low voltage disconnect for starter battery protection. | 0 |
| 1900996 | O | Jump start terminals under hood. | 12 |
| 1901018 | O | Remote PTO/Throttle, 12-Pin, 250K, Back of Cab OR Back of Sleeper, J1939, Remote Control Provision | 0 |
| Transmission & Clutch | | | |
| 2016158 | O | Transmission: Allison 4500RDS 6-speed | 280 |

| Sales Code | Std/Opt | Description | Weight |
|------------|---------|---|--------|
| 3407050 | S | Dual Rear Hubs: Aluminum hub pilot 46K 11-1/4 in. bolt circle. | 0 |
| 3441972 | S | ConMet PreSet Plus Hub package; dual rear axle. | 0 |
| 3465002 | S | Dual Rear axle automatic slack adjusters. | 0 |
| 3485209 | O | Spring Brake: 3030 high output dual. | 0 |
| 3495226 | O | Bendix 4S/4M anti-lock brake system. | 0 |
| 3500006 | O | Inverted chambers for 16-1/2 x 7 in. brakes; Replaces standard mount w/ higher mount. | 0 |
| 3500037 | O | Interaxle driveline:1 Dana 1710 Series | 0 |
| 3749203 | O | Rear suspension: Tandem Chalmers 854-46-L-HS 46K. 54 in. axle spacing. High center of gravity application. Unladen Height: 11.3 in. Laden Height: 9.6 in. | 226 |
| 3830145 | O | Delete standard heavy-duty air springs for rear suspension. | -28 |

Tires & Wheels

| | | | |
|---------|---|--|-----|
| 4077537 | O | Front tires: Bridgestone M870 315/80R22.5 20PR All Position | 94 |
| 4277493 | O | Rear tires: Bridgestone M770 11R24.5 14PR. 44.2 in. diameter, all position. 20.6 in. SLR. Code is priced per pair of tires. | 208 |
| 4900008 | O | Rear Tire Quantity: 8 | 0 |
| 5045268 | O | Front Wheel: Alcoa 89U63 22.5X9 AL Ultra ONE Wheel. | -39 |
| 5242315 | O | Rear Wheel: Accuride 50641 24.5X8.25 steel ACCU-LTE. Steel Armor(TM) powder coat, hub-pilot mount. 7400lb. maximum rating. 5-hand hole. | 64 |
| 5853906 | S | Powder coat white steel wheel. Use in conjunction with front, dual front, rear, spare or lift axle wheel code(s). All wheels on chassis must have same finish color. | 0 |
| 5900008 | O | Rear Wheel/Rim Quantity: 8 | 0 |

Frame & Equipment

| | | | |
|---------|---|--|-----|
| 6056400 | O | Frame Rails: 10-3/4 x 3-1/2 x 3/8in. Steel 285in. to 336 in. Truck frame weight is 3.48 lb.-in. per pair of rails. Section modulus is 17.80, RBM is 2,132,000 in.-lbs per rail. Frame rail availability may be restricted based upon application, axle/suspension capacity, fifth wheel setting, or component/dimensional specifications. The results of the engineering review may result in a change to the requested frame rail. If a change is required Kenworth Application Engineering will advise the dealer of the appropriate material specification for a substitute rail. | 379 |
| 6302461 | O | Bumper: Tapered chrome steel channel. Requires a bumper setting code. | 63 |

| Sales Code | Std/Opt | Description | Weight |
|------------|---------|---|--------|
| 8108011 | S | Cab HVAC - Day Cab and 40in Sleeper System With Defrost, A/C, and 48,000 BTU/hr Heater. Includes automatic temperature control with one touch defrost operation and dash mounted cab temperature and solar intensity sensors. Pleated fresh air filter and cabin recirculation air filter standard. The Kenworth HVAC system is designed to provide optimal heating and cooling in all operating environments without need for additional insulation. Cab HVAC without sleeper heater AC is available with 40in sleeper. | 0 |
| 8201013 | S | Steering wheel: 18 in. 4-spoke. | 0 |
| 8201051 | O | Column Mtd Retarder Control, RH Side Use with Manual & Allison Transmissions Only. | 0 |
| 8201200 | S | Adjustable telescoping tilt steering column. | 0 |
| 8203060 | O | 5 sets of keys. Replaces standard 2 sets of keys. | 0 |
| 8208495 | O | Two spare switches: Wired to power. | 0 |
| 8222712 | O | Gauge: Fuel filter restriction gauge. | 0 |
| 8282007 | S | Kenworth Driver Performance Center:5in Full Color high resolution Thin Film Transistor (TFT) active matrix display with advanced driver information including fuel economy performance, outside air temp, clock, odometer and trip, engine hour meter, ignition timer, engine RPM, general truck information, diagnostics, and gear display. All Highline functionality is accessed via the Kenworth MCS providing intuitive control at the drivers fingertips. Also includes Dark Cabin functionality. When activated, the only interior light that will function when a door is opened is the door courtesy lamp. | 0 |
| 8282013 | S | Kenworth instrumentation and control package with 9 standard easy-read gauges: includes speedometer, tachometer, fuel gauge, engine coolant temp, engine oil pressure, voltmeter, dual air pressure, air application pressure and DEF gauge. All accessory controls utilize electronically activated solenoids that include advanced vehicle protection interlocks. | 0 |
| 8291011 | O | Warning Light and Audible: Drivers Side Seatbelt A telltale and audible warning activates when vehicle speed > 10 mph and driver side seatbelt is not buckled. | 0 |
| 8300008 | S | Interior color: Slate Gray | 0 |
| 8330102 | S | Interior package: Vantage daycab Includes durable headliner and vinyl sidewalls with geometric patterned trim and anodized aluminum accents throughout. Convenient overhead storage cubbies, full size glove box, two center console cupholders, and large door pad map pocket. Standard LH/RH power windows, electric door locks, interior LED lighting, nighttime-friendly red ambient lighting for dash and footwell, and door mounted courtesy light. Includes two standard 12V power outlets. Driver sunvisor includes strap. | 0 |
| 8390634 | S | Rubber floormat | 0 |
| 8410200 | O | Driver Seat: GT701 HB with Vinyl material. | 0 |

| Sales Code | Std/ Opt | Description | Weight |
|---------------------------------|----------|--|--------|
| | | heated mirrors, 7in X 13in with cab color mirror shell and black mirror arms. Also includes LH/RH heated 6in X 7in convex mirrors. Mirror brackets set for 8-1/2 ft load width. Mirror controls located on driver side door pad. | |
| 8871446 | S | Rear cab stationary window 19in x 36in | 0 |
| 8890101 | S | One-piece bonded-in windshield with curved glass. Standard. | 0 |
| 8890348 | O | Wheelwell Fender Extension: 4.5 inches | 1 |
| 8890876 | S | Kenworth Cab/Sleeper Air Suspension. | 0 |
| Lights & Instruments | | | |
| 9010553 | S | Headlamps: SAE Dual Halogen Complex Reflector | 0 |
| 9022137 | S | Marker Lights: Five, rectangular, LED | 0 |
| 9030016 | S | Turn Signal Lights: Flush mounted LED mounted at top of fender wheel arc | 0 |
| 9030052 | S | LED Stop, Turn, Tail: With Two LED Backup Lights and With An LED License Plate. | 0 |
| 9080128 | O | Dual Revolving Amber Roof Lights: Centered over cab door w/ stainless steel bracket. | 15 |
| 9090039 | S | Marker Lights: Interrupter Switch. Included in Turn Signal For All Models Except T3. The T3 Switch Is In The Dash. | 0 |
| 9090052 | O | Brake Lights on when Engine Brake Active. Can only be selected when chassis also has engine brake. Cannot be used with options to delete engine brake. | 0 |
| 9090126 | O | Electric Backup Alarm: Meets SAE J994 & OSHA requirements. | 4 |
| 9090849 | O | Polyswitches replacing fuses. Switch will automatically reset after removal of excess load. | 0 |
| Air Equipment | | | |
| 9101215 | S | Air Dryer Bendix AD-IS heated Puraguard | 0 |
| 9108001 | S | Moisture ejection valve w/ pull cable drain. | 0 |
| 9110020 | O | Full truck kit: Gladhands mounted at end-of-frame. Seven-way female receptacle mounted at end-of-frame in taillamp bracket. Kit includes dash mounted trailer air supply valve, trailer hand control valve, and hoses/fittings for the valves. Dash mounted parking brake valve, tractor protection valve, and spring brake inversion/relay valves are standard. | 15 |
| 9140020 | S | Nylon air tubing in frame & cab, excluding hoses subject to excessive heat or flexing. | 0 |
| 9140200 | O | Delete trailer hand valve. Must code for tractor kit. | 0 |



Total Weight

16,779

Prices and Specifications Subject to Change Without Notice.

Unpublished options may require review/approval.

Dimensional and performance data for unpublished options may vary from that displayed in CRM.

PRICING DISCLAIMER

While we make every effort to maintain the web site to preserve pricing accuracy, prices are subject to change without notice. Although the information in this price list is presented in good faith and believed to be correct at the time of printing, we make no representations or warranties as to the completeness or accuracy of this information. We reserve the right to change, delete or otherwise modify the pricing information which is represented herein without any prior notice. We carefully check pricing specifications, but occasionally errors can occur, therefore we reserve the right to change such prices without notice. We disclaim all liability for any errors or omissions in the materials. In no event will we be responsible for any damages of any nature whatsoever from the reliance upon information from these materials. Please check your order prebills to confirm your pricing information